



The photograph may not match the reference exactly. Please read the product description to identify the finish.

TECHNICAL CHARACTERISTICS



Product Model:	T-190VLED40-16	T-190VLED60-32	T-190VLED40-56B	T-190VLED60-84B
IP Protection degrees:	IP65			
IK Protection degrees:	IK08			
Light source:	16 x LED CREE / 16 x LUXEON 5050	32 x LED CREE / 32 x LUXEON 5050	56 x LUXEON 3030	84 x LUXEON 3030
Total power consumption:	40W	60W	40W	60W
Luminous Flux:	3900-4900Lm	6300-7860Lm	4000Lm	5700Lm
Luminous efficiency:	95-125Lm/w			
Color temperature:	4000K as standard. Optimal 2700K, 3000K & 5700K. Amber LED available			
Voltage/Frequency:	100-240V/50-60Hz			
Warranty(Years):	5			
Units per box:	1			
Net Weight(Kg)	9.5	9.5	9.5	9.5

MATERIALS / FINISHES

Structure material: High purity aluminium	aiffuser material: Glass
Structure finish: Silver	Diffuser finish: Transparent

GEAR

Multi-voltage electronic gear included (110-240 V / 50-60 Hz)

Lm^(N): Nominal flow of light in actual working conditions. Its actual flow will depend on the environmental conditions and the efficiency of the optics and/or diffuser.