


B-13
12W



B-13B
25W



简述 Description



- 铝压铸盖帽，铝合金拉伸灯体，可根据需要截取不同高度
- 高透明PC扩散罩，能有效防止发黄老化，并具有很好的出光视觉效果
- 防紫外线聚氨酯粉末喷涂表面，耐腐蚀可达1000小时以上
- 无生物蓝光危害风险，符合EN62471: 2008 标准
- 灯具表面最高温度不超过50度，安全可靠

- Aluminum die casting cover, extruded aluminum alloy body, it can be cut different heights.
- High transparent PC diffuser, it can effectively prevent yellowing and aging. with high visual comfort light distribution.
- Surface anti-ultraviolet pure polyester powder painting, Corrosion resistance can be more than 1000 hours.
- No photo-biological risk, in accordance with EN 62471:2008.
- The maximum surface temperature of all accessible part under 50 degrees for safety and reliable.

技术参数 Technology data



B-13								
Code	Power	LED Qty	Input Voltage	Lumen	Beam Angle	Packing Size	Pcs/Box	
LED chips - 2835								
B-13LED12-42B	12W	42	100V-240V	1080	120°	275*275*260	4	

B-13B								
Code	Power	LED Qty	Input Voltage	Lumen	Beam Angle	Packing Size	Pcs/Box	
LED chips - 2835								
B-13BLED25-56B	25W	56	100V-240V	2250	120°	375*375*340	4	

延伸产品 More in family



C-13
Bollard Lighting: 12W.
Page. 378



C-13BS
Bollard Lighting: 25W.
Page. 380