





B-03 / B-15M



B-03
9W



B-15M
15W


简述 Description



- 灯具外壳采用铝合金压铸成型
- 超白磨砂钢化玻璃，具有高视觉舒适性和均匀配光
- 防紫外线聚氨酯粉喷涂表面，耐腐蚀可以达1000小时以上
- 无生物蓝光危害风险，符合EN62471: 2008 标准
- 灯具表面最高温度不超过50度，安全可靠


- The lighting body made by die-casting aluminium.
- Super white tempered glass, with high visual comfort and uniform lighting distribution.
- Surface anti-ultraviolet pure polyester powder painting, Corrosion resistance can be more than 1000 hours.
- No photo-biological risk, in accordance with EN 62471:2008.
- The maximum surface temperature of all accessible part under 50 degrees for safety and reliable.

技术参数 Technology data



B-03

Code	Power	LED Qty	Input Voltage	Lumen	Beam Angle	Packing Size	Pcs/Box
LED chips - 2835							
B-03LED9-18B	9W	9*2	100V-240V	716	100°	285*245*230	4



B-15M

Code	Power	LED Qty	Input Voltage	Lumen	Beam Angle	Packing Size	Pcs/Box
LED chips - 2835							
B-15MLED15-72B	15W	36*2	100V-240V	1275	100°	330*250*270	6