



The photograph may not match the reference exactly. Please read the product description to identify the finish.

TECHNICAL CHARACTERISTICS



Product Model:	T-190NLED40-128B	T-10BLED60-128B
IP Protection degrees:	IP65	IP65
IK Protection degrees:	IK09	IK09
Light source:	128 x SMD 2835	128 x SMD 2835
Total power consumption:	40W	60W
Luminous Flux:	4400Lm	6600Lm
Luminous efficiency:	110Lm/w	
Color temperature:	4000K as standard. Optimal 2700K, 3000K & 5700K. Amber LED available	
Voltage/Frequency:	100-240V/50-60Hz	
Warranty(Years):	5	
Units per box:	1	
Net Weight(Kg)	7.4	7.4
Aerodynamic resistance (CxS)	0.138	

MATERIALS / FINISHES

Structure material: High purity aluminium	diffuser material: Glass
Structure finish: Silver	Diffuser finish: Transparent

GEAR

Multi-voltage electronic gear included (110-240 V / 50-60 Hz)

Lm^(N): Nominal flow of light in actual working conditions. Its actual flow will depend on the environmental conditions and the efficiency of the optics and/or diffuser.

500

High purity aluminum

530

Transparent PC

High purity aluminum

$\phi 60 \times 60$

