



方形壁灯 Square Wall Lighting



B-242
12W




B-242L
25W



B-242W
12W

简述 Description



- 铝压铸灯体外壳，超白钢化玻璃，具有高视觉舒适性和均匀光输出
- 高性能LED芯片，驱动有0-10V / DALI / 编程电源选择
- 灯具采用LED 模组式设计，模块式电器部件，安装更换方便
- 防紫外线聚氨酯塑粉喷涂表面，耐腐蚀可以达到1000小时以上
- 无生物蓝光危害风险，符合EN62471: 2008 标准
- 灯具表面最高温度不超过50度，安全可靠
- KLED智能感应设备，通过监控行人及车流量识别，自动调节灯具光通量输出

- Die-casting aluminium body, super white tempered glass, with high visual comfort and uniform lighting distribution.
- High quality LED chips, Driver with 0-10V/DALI/programmed options.
- LED module designed, Integrated components which is easy to install and replace.
- Surface anti-ultraviolet pure polyester powder painting, Corrosion resistance can be more than 1000 hours.
- No photo-biological risk, (no risk linked to infrared, blue light and UV radiation) in accordance with EN 62471:2008.
- The maximum surface temperature of all accessible part under 50 degrees for safety and reliable.
- Kled intelligent sensing equipment can automatically adjust the luminous flux output by monitoring pedestrian and traffic flow identification.

技术参数 Technology data

B-242		Code	Power	LED Qty	Input Voltage	Lumen	Beam Angle	Packing Size	Pcs/Box
		LED chips - 2835 B-242LED12-48	12W	48	220V-240V	1500	120°	230*390*170	4
B-242L		Code	Power	LED Qty	Input Voltage	Lumen	Beam Angle	Packing Size	Pcs/Box
		LED chips - 3535/5050 B-242LLED25-24	25W	24	220V-240V	3750	T25/T50/T90/T1	230*390*380	4
B-242W		Code	Power	LED Qty	Input Voltage	Lumen	Beam Angle	Packing Size	Pcs/Box
		LED chips - 2835 B-242WLED12-48	12W	48	220V-240V	1500	120°	440*270*225	2