



B-16 Series




B-16S/16SD
9W/9W*2
□ □



B-16M/16MD
20W/20W*2
□ □


简述 Description



- 铝压铸灯具底座及散热组件，铝合金拉伸外壳
- 超白丝印钢化玻璃，具有高视觉舒适性和均匀配光，出光角可以选
- 防紫外线聚氨酯塑粉喷涂表面，耐腐蚀可以达1000小时以上
- 无生物蓝光危害风险，符合EN62471: 2008 标准
- 灯具表面最高温度不超过50度，安全可靠


- Aluminum die casting base and heatsink, extruded aluminum alloy body.
- Super white screen printing tempered glass. with high visual comfort light distribution, different optical be option.
- Surface anti-ultraviolet pure polyester powder painting, Corrosion resistance can be more than 1000 hours.
- No photo-biological risk, in accordance with EN 62471:2008.
- The maximum surface temperature of all accessible part under 50 degrees for safety and reliable.

技术参数 Technology data



B-16S/16SD

Code	Power	LED Qty	Input Voltage	Lumen	Beam Angle	Packing Size	Pcs/Box
LED chips - 3535							
B-16SLED9-4A	9W	4	100V-240V	950	25°/40°	305*235*190	4
B-16SDLED18-8A	18W	4*2	100V-240V	1900	25°/40°	305*235*190	4



B-16M/16MD

Code	Power	LED Qty	Input Voltage	Lumen	Beam Angle	Packing Size	Pcs/Box
LED chips - 3535							
B-16MLED20-9A	20W	9	100V-240V	2000	25°/40°	385*345*225	4
B-16MDLED40-18A	40W	9*2	100V-240V	4000	25°/40°	385*345*225	4